

GOK

Komponenten • Lösungen • Systeme



Outlet connectors

Outlet connectors

	<table border="1"> <tr> <td>Commercial name</td> <td>M20 x 1.5 M</td> </tr> <tr> <td>Designation to standard*</td> <td>H.1</td> </tr> <tr> <td>Country</td> <td>CH, EU, RU</td> </tr> </table>	Commercial name	M20 x 1.5 M	Designation to standard*	H.1	Country	CH, EU, RU	<table border="1"> <tr> <td>A</td> <td>M20 x 1.5 rh</td> </tr> </table>	A	M20 x 1.5 rh																						
Commercial name	M20 x 1.5 M																															
Designation to standard*	H.1																															
Country	CH, EU, RU																															
A	M20 x 1.5 rh																															
	<table border="1"> <tr> <td>Commercial name</td> <td>Male thread connector (G 1/2-FD)</td> </tr> <tr> <td>Designation to standard*</td> <td>H.3</td> </tr> <tr> <td>Country</td> <td>GR, IT, RU, SI</td> </tr> </table>	Commercial name	Male thread connector (G 1/2-FD)	Designation to standard*	H.3	Country	GR, IT, RU, SI	<table border="1"> <tr> <td>A</td> <td>G 1/2</td> </tr> <tr> <td>B</td> <td>12.0 mm</td> </tr> </table>	A	G 1/2	B	12.0 mm																				
Commercial name	Male thread connector (G 1/2-FD)																															
Designation to standard*	H.3																															
Country	GR, IT, RU, SI																															
A	G 1/2																															
B	12.0 mm																															
	<table border="1"> <tr> <td>Commercial name</td> <td>Ball-cone connector</td> </tr> <tr> <td>Designation to standard*</td> <td>H.4, H.6, H.5</td> </tr> <tr> <td>Country</td> <td>AT, CH, CZ, DE, PL, RU, SI</td> </tr> </table>	Commercial name	Ball-cone connector	Designation to standard*	H.4, H.6, H.5	Country	AT, CH, CZ, DE, PL, RU, SI	<table border="1"> <tr> <td>A</td> <td>G 1/4 lh M G 3/8 lh M G 1/2 lh M</td> </tr> </table>	A	G 1/4 lh M G 3/8 lh M G 1/2 lh M																						
Commercial name	Ball-cone connector																															
Designation to standard*	H.4, H.6, H.5																															
Country	AT, CH, CZ, DE, PL, RU, SI																															
A	G 1/4 lh M G 3/8 lh M G 1/2 lh M																															
	<table border="1"> <tr> <td>Commercial name</td> <td>Female thread</td> </tr> <tr> <td>Designation to standard*</td> <td>H.7</td> </tr> <tr> <td>Country</td> <td>international</td> </tr> </table>	Commercial name	Female thread	Designation to standard*	H.7	Country	international	<table border="1"> <tr> <td>A</td> <td>Rp 1/4 F to Rp 2 F EN 10226-1</td> </tr> </table>	A	Rp 1/4 F to Rp 2 F EN 10226-1																						
Commercial name	Female thread																															
Designation to standard*	H.7																															
Country	international																															
A	Rp 1/4 F to Rp 2 F EN 10226-1																															
	<table border="1"> <tr> <td>Commercial name</td> <td>Compression fitting</td> </tr> <tr> <td>Designation to standard*</td> <td>H.8 H.9</td> </tr> <tr> <td>Country</td> <td>international</td> </tr> </table>	Commercial name	Compression fitting	Designation to standard*	H.8 H.9	Country	international	<table border="1"> <tr> <td>12 mm</td> <td>A/Flats</td> <td>22</td> </tr> <tr> <td>15 mm</td> <td>A/Flats</td> <td>27</td> </tr> <tr> <td>18 mm</td> <td>A/Flats</td> <td>32</td> </tr> <tr> <td>22 mm</td> <td>A/Flats</td> <td>36</td> </tr> <tr> <td>28 mm</td> <td>A/Flats</td> <td>41</td> </tr> <tr> <td>35 mm</td> <td>A/Flats</td> <td>50</td> </tr> <tr> <td>8 mm</td> <td>A/Flats</td> <td>17</td> </tr> <tr> <td>10 mm</td> <td>A/Flats</td> <td>19</td> </tr> </table>	12 mm	A/Flats	22	15 mm	A/Flats	27	18 mm	A/Flats	32	22 mm	A/Flats	36	28 mm	A/Flats	41	35 mm	A/Flats	50	8 mm	A/Flats	17	10 mm	A/Flats	19
Commercial name	Compression fitting																															
Designation to standard*	H.8 H.9																															
Country	international																															
12 mm	A/Flats	22																														
15 mm	A/Flats	27																														
18 mm	A/Flats	32																														
22 mm	A/Flats	36																														
28 mm	A/Flats	41																														
35 mm	A/Flats	50																														
8 mm	A/Flats	17																														
10 mm	A/Flats	19																														

A = Thread designation / B = Minimum diameter / C = Length of hose nozzle / D = Maximum diameter
E = Inner diameter / F = Thread length

*Designation according to EN 16129 annex H / **Designation GOK factory standard

Outlet connectors

	<table border="1"> <tr> <td>Commercial name</td> <td>G 3/4 nut G 1 nut</td> </tr> <tr> <td>Designation to standard*</td> <td>H.10</td> </tr> <tr> <td>Country</td> <td>CZ, DE, PL, SI</td> </tr> </table>	Commercial name	G 3/4 nut G 1 nut	Designation to standard*	H.10	Country	CZ, DE, PL, SI	<table border="1"> <tr> <td>A</td> <td>G 3/4 ISO 228-1 G 1 ISO 228-1</td> </tr> <tr> <td>B</td> <td>14.0 mm 15.0 mm</td> </tr> <tr> <td>C</td> <td>--</td> </tr> <tr> <td>D</td> <td>21.0 mm 27.5 mm</td> </tr> </table>	A	G 3/4 ISO 228-1 G 1 ISO 228-1	B	14.0 mm 15.0 mm	C	--	D	21.0 mm 27.5 mm
Commercial name	G 3/4 nut G 1 nut															
Designation to standard*	H.10															
Country	CZ, DE, PL, SI															
A	G 3/4 ISO 228-1 G 1 ISO 228-1															
B	14.0 mm 15.0 mm															
C	--															
D	21.0 mm 27.5 mm															
	<table border="1"> <tr> <td>Commercial name</td> <td>Compression / separation connector (PTV)</td> </tr> <tr> <td>Designation to standard*</td> <td>H.10</td> </tr> <tr> <td>Country</td> <td>DE</td> </tr> </table>	Commercial name	Compression / separation connector (PTV)	Designation to standard*	H.10	Country	DE	<table border="1"> <tr> <td></td> <td>15.0 mm x R 1/2 EN 10226-1</td> </tr> <tr> <td></td> <td>18.0 mm x R 1/2 EN 10226-1</td> </tr> <tr> <td></td> <td>22.0 mm x R 1/2 EN 10226-1</td> </tr> </table>		15.0 mm x R 1/2 EN 10226-1		18.0 mm x R 1/2 EN 10226-1		22.0 mm x R 1/2 EN 10226-1		
Commercial name	Compression / separation connector (PTV)															
Designation to standard*	H.10															
Country	DE															
	15.0 mm x R 1/2 EN 10226-1															
	18.0 mm x R 1/2 EN 10226-1															
	22.0 mm x R 1/2 EN 10226-1															
	<table border="1"> <tr> <td>Commercial name</td> <td>Solder / separation connector (LTV)</td> </tr> <tr> <td>Designation to standard*</td> <td>H.10</td> </tr> <tr> <td>Country</td> <td>CZ, DE, SI</td> </tr> </table>	Commercial name	Solder / separation connector (LTV)	Designation to standard*	H.10	Country	CZ, DE, SI	<table border="1"> <tr> <td></td> <td>15.0 mm x R 1/2 EN 10226-1</td> </tr> <tr> <td></td> <td>18.0 mm x R 1/2 EN 10226-1</td> </tr> <tr> <td></td> <td>22.0 mm x R 1/2 EN 10226-1</td> </tr> </table>		15.0 mm x R 1/2 EN 10226-1		18.0 mm x R 1/2 EN 10226-1		22.0 mm x R 1/2 EN 10226-1		
Commercial name	Solder / separation connector (LTV)															
Designation to standard*	H.10															
Country	CZ, DE, SI															
	15.0 mm x R 1/2 EN 10226-1															
	18.0 mm x R 1/2 EN 10226-1															
	22.0 mm x R 1/2 EN 10226-1															
	<table border="1"> <tr> <td>Commercial name</td> <td>NPT thread</td> </tr> <tr> <td>Designation to standard*</td> <td>H.11</td> </tr> <tr> <td>Country</td> <td>international</td> </tr> </table>	Commercial name	NPT thread	Designation to standard*	H.11	Country	international	<table border="1"> <tr> <td>A</td> <td>1/16 NPT F to 2 NPT F ANSI/ASME B.1.20.1</td> </tr> </table>	A	1/16 NPT F to 2 NPT F ANSI/ASME B.1.20.1						
Commercial name	NPT thread															
Designation to standard*	H.11															
Country	international															
A	1/16 NPT F to 2 NPT F ANSI/ASME B.1.20.1															
	<table border="1"> <tr> <td>Commercial name</td> <td>Tapered female thread</td> </tr> <tr> <td>Designation to standard*</td> <td>H.19</td> </tr> <tr> <td>Country</td> <td>international</td> </tr> </table>	Commercial name	Tapered female thread	Designation to standard*	H.19	Country	international	<table border="1"> <tr> <td>A</td> <td>Rc 1/4 F to Rc 2 F EN 10226-2</td> </tr> </table>	A	Rc 1/4 F to Rc 2 F EN 10226-2						
Commercial name	Tapered female thread															
Designation to standard*	H.19															
Country	international															
A	Rc 1/4 F to Rc 2 F EN 10226-2															

A = Thread designation / **B** = Minimum diameter / **C** = Length of hose nozzle / **D** = Maximum diameter
E = Inner diameter / **F** = Thread length

*Designation according to EN 16129 annex H / **Designation GOK factory standard

Outlet connectors

	Commercial name	M20 x 1.5 nut	A	M20 x 1.5 rh	A/Flats 23
	Designation to standard*	H.20			
	Country	CH, EU, RU			
	Gasket material	FKM			

	Commercial name	Parallel female thread	A	G 1/4 F to G 1 F	ISO 228-1
	Designation to standard*	H.22			
	Country	international			

	Commercial name	Hose nozzle (Tülle8-K)	A	--
	Designation to standard*	H.50	B	8.0 mm
	Country	BE, CH, FR, GB, IT, PT, RU, SE, SI	C	max. 24.0 mm
			D	10.0 mm

	Commercial name	Hose nozzle (Tülle13-L)	A	--
	Designation to standard*	H.52	B	13.0 mm
	Country	BE, CH, FR, GB, PT, RU, SE, SI	C	max. 48.5 mm
			D	14.0 mm

	Commercial name	Hose nozzle (Tülle8-L)	A	--
	Designation to standard*	H.53	B	8.0 mm
	Country	BE, CH, FR, GB, PT, RU, SE, SI	C	max. 29.5 mm
			D	10.0 mm

A = Thread designation / B = Minimum diameter / C = Length of hose nozzle / D = Maximum diameter
E = Inner diameter / F = Thread length

*Designation according to EN 16129 annex H / **Designation GOK factory standard

Outlet connectors

	Commercial name	Hose nozzle (Tülle13-K)	A	--
	Designation to standard*	H.54	B	13.0 mm
	Country	BE, CH, FR, GB, PT, RU, SE, SI	C	max. 44.5 mm
			D	14.0 mm
	Commercial name	M22 x 1.5 lh and M30 x 1.5 lh	A	M22 x 1.5 lh M30 x 1.5 lh
	Designation GOK**	Y.1		
	Country	DE		
	Commercial name	G 3/4 M	A	G 3/4 ISO 228-1
	Designation GOK**	Y.5	E	16.0 mm
	Country	DE, PL	F	thread length 8.0 mm
	Commercial name	Large cylinder male thread (GF) Connector 1 (DIN 477)	A	W21.8 x 1/14 LH
	Designation GOK**	Y.6	B	13.0 mm
	Country	AT, CZ, DE, DK, FI, PL, RU, SI		

A = Thread designation / B = Minimum diameter / C = Length of hose nozzle / D = Maximum diameter
E = Inner diameter / F = Thread length

*Designation according to EN 16129 annex H / **Designation GOK factory standard